



"THE RIGHT WAY TO RESTORE WOOD"

Conforms to HCS 2012 - United States

# SAFETY DATA SHEET

## STRONGBOND EPOXY WOOD SEALER — Part A

### 1. Product and Company Identification

**Product Name:** StrongBond Epoxy Wood Sealer (Part A)

**Product Use:** Epoxy Wood Sealer

**Company Identification:**

NEW ENTERPRISES, CO.  
P.O. Box 11976  
San Rafael, CA 94912  
(415) 722-9098

**Emergency Phone:**

CHEM-TEL  
1-800 255-3924 (24 hrs)

### 2. Hazards Identification (Part A)

**GHS Classification**

Health	Physical	Environmental
Skin Irritant Cat 2 Eye Irritant Cat 2B Skin Sens 1	Not Classified	Not Classified

GHS Label:

Warning:



Eye Irritant  
Skin Irritant  
Skin Sensitizer

**Emergency Overview**

May cause skin sensitization  
Causes skin and eye irritation  
Wash skin thoroughly after handling  
Avoid breathing fume/gas/mist/vapors/spray  
Wear protective gloves/ protective clothing/ eye protection/ face protection  
Use outdoors or in a well-ventilated area

**Primary Route of Exposure**

Eyes, skin and oral

**Carcinogenicity**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA

3. Composition/ Information on Ingredients (Part A)

<u>CAS Number</u>	<u>Content %</u>	<u>Chemical Name</u>
25085-99-8	40 - 60	Diglycidyl Ether of Bisphenol A
17557-23-2	30 - 50	Neopentyl Glycol Diglycidyl Ether
68609-97-2	3 - 7	Glycidyl Ether

4. First Aid Measures (Part A)

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

5. Fire Fighting Measures (Part A)

Flash Point: N/D  
Flammable Limits: N/A

Extinguisher Media  
Carbon Dioxide, Dry Chemical, Water Fog

Unusual Fire and Explosion Hazard  
None known. Thermal Decomposition can be formed.

Special Fire Fighting Procedures  
Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

6. Accidental Release Measures (Part A)

**Personal Precautions:**  
Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

**Environmental Precautions**  
Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

7. Handling and Storage (Part A)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

8. Exposure Control and Personal Protection (Part A)

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

**Personal Protective Equipment**

**Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

**Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

**Skin/Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

**Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

9. Physical and Chemical Properties (Part A)

Appearance:	Clear Liquid
Evaporation Rate:	N/D
Odor:	Slight Odor
Solubility in Water:	Insoluble
Specific Gravity(g/cc):	N/D
Vapor Density(air = 1):	Non-volatile
Vapor Pressure:	N/D
VOC Content:	22 g/L when mixed (See section 9 of Sealer Part B)
pH:	N/D
Boiling Point:	N/D

10. Stability and Reactivity (Part A)

Stability:	Stable
Thermal Decomposition:	Can yield CO, CO <sub>2</sub> and organic Nitrogen compounds
Incompatibility:	Strong acids, peroxides, and other oxidizing agents
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelf life.

11. Toxicological Information (Part A)

Acute Oral Toxicity:	Not Determined
Acute Dermal Toxicity:	Not Determined
Acute Inhalation Toxicity:	Not Determined

**Skin Irritation:**

Irritating to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Irritating to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Not Determined

**Sensitization:**

May cause allergic skin reaction

The product has not been tested. The statement has been derived from the properties of the individual components.

STOT – Single Exposure

Not Determined

STOT – Repeated Exposure

Not Determined

Carcinogenicity Classification:

No known carcinogens

---

**12. Ecological Information (Part A)**

**Fish:**

Diglycidyl Ether of Bisphenol A:

Fathead minnow/LC50 (96hrs): >3.1mg/l

**Aquatic Invertebrates:**

Diglycidyl Ether of Bisphenol A:

Water Flea Daphnis/EC 50 (48hrs): > 1.4mg/l

**Algae:**

No Data Available

**Microorganisms:**

Diglycidyl Ether of Bisphenol A:

Bacteria, (Growth inhibition)/IC50 (18hrs): > 42.6mg/l

**Mobility:**

Considering the use of the substance, it is unlikely that significant environmental exposure in the air or water will arise.

---

**13. Disposal Considerations (Part A)**

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

---

**14. Transportation Information (Part A)**

This product is not regulated as a hazardous material for transportation.

---

15. Regulatory Information (Part A)

HMIS Rating	
Health	2
Flammability	1
Physical Hazard	0
PPE	B

NFPA Rating



Hazard Rating: 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

Federal Regulations

CERCLA RQ

SARA Title 311/312

Not Determined

CA Prop 65

Not Regulated

TSCA

Listed or Exempt

State Regulations:

State RTK  
NJ, MA, PA

CAS#  
25085-99-8

Chemical Name  
Diglycidyl Ether of Bisphenol A

16. Other Information (Part A)

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, New Enterprises Co. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.



"THE RIGHT WAY TO RESTORE WOOD"

Conforms to HCS 2012 - United States

# SAFETY DATA SHEET

STRONGBOND EPOXY WOOD SEALER — Part B

## 1. Product and Company Identification

**Product Name:** StrongBond Epoxy Wood Sealer (Part A)

**Product Use:** Epoxy Wood Sealer

**Company Identification:**  
NEW ENTERPRISES, CO.  
P.O. Box 11976  
San Rafael, CA 94912  
(415) 722-9098

**Emergency Phone:**  
CHEM-TEL  
1-800 255-3924 (24 hrs)

## 2. Hazards Identification (Part B)

GHS Classification

Health	Physical	Environmental
Skin Corrosion Cat 1 Serious Eye Damage Cat 1 Reproductivetoxicity Cat 2	Not Classified	Toxic to Aquatic Life Cat-2

GHS Label:

Danger:



Corrosive to skin and eyes  
Skin Irritant



Reproductive toxicity

### Emergency Overview

- Causes skin burns
- Causes severe eye damage
- Suspected of damaging fertility
- May cause skin sensitization
- Wash skin thoroughly after handling
- Avoid breathing fume/gas/mist/vapors/spray
- Wear protective gloves/ protective clothing/ eye protection/ face protection
- Use outdoors or in a well-ventilated area
- Avoid contact during pregnancy/while nursing

**Primary Route of Exposure**  
Eyes, skin and oral

### **Carcinogenicity**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspect carcinogen by NTP, IARC, Prop 65 or OSHA

3. Composition/ Information on Ingredients (Part B)

<u>CAS Number</u>	<u>Content%</u>	<u>Chemical Name</u>
140-31-8	30 - 40	N- Aminoethylpiperazine
68953-36-6	10 - 25	Modified Polyamido Amine
84852-15-3	30 - 40	Nonylphenol
112-24-3	10 - 25	Triethylenetetramine

4. First Aid Measures (Part B)

**Inhalation:** Move to fresh air; give oxygen if breathing is difficult. Call a physician if symptoms persist.

**Eyes:** Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician if symptoms persist.

**Skin:** Remove contaminated clothing. Wash with mild soap and water. Get medical attention if skin irritation or dermatitis persists.

**Ingestion:** Give plenty of water. DO NOT induce vomiting. Call a physician immediately.

**Other:** Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure. If sensitization occurs, future contact with the material should be avoided.

5. Fire Fighting Measures (Part B)

Flash Point: N/D

Flammable Limits: N/A

**Extinguisher Media**

Carbon Dioxide, Dry Chemical, Water Fog

**Unusual Fire and Explosion Hazard**

None known. Thermal Decomposition can be formed.

**Special Fire Fighting Procedures**

Firefighters must wear self-contained breathing apparatus and full protective clothing to prevent contact with toxic and/or irritating fumes.

6. Accidental Release Measures (Part B)

**Personal Precautions:**

Avoid all personal contact. In enclosed areas, cleanup personnel should wear self-contained breathing apparatus.

**Environmental Precautions**

Cover spills with sawdust, vermiculite, or other absorbent material to minimize spreading of the material before collecting.

7. Handling and Storage (Part B)

**Handling:** Avoid contact with eyes, skin and clothing. Avoid inhalation of vapors. Use with adequate ventilation. Use appropriate personal protection equipment (Section 8). Wash thoroughly after handling.

**Storage:** Store in a cool dry place away from direct sunlight. Keep from freezing. Recommended storage temperature range in between 4 °C and 35 °C (40°F and 95° F).

**8. Exposure Control and Personal Protection (Part B)**

**Engineering Measures:** Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.

**Personal Protective Equipment**

**Respiratory Protection**

None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up.

**Eye/Face Protection**

Wear splash proof chemical goggles/ full face shield if there is a potential for splashing.

**Skin / Body Protection**

Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure.

**Other Protective Clothing or Equipment**

Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

**9. Physical and Chemical Properties (Part B)**

Appearance:	Amber Liquid
Evaporation Rate:	N/A
Odor:	Slight Odor
Solubility in Water:	Insoluble
Specific Gravity(g/cc):	N/D
Vapor Density(air = 1):	N/D
Vapor Pressure:	N/D
VOC Content:	22 g/L (tested per EPA, CFR 40, Part 60, method 24)
pH:	N/D
Boiling Point:	N/A

**10. Stability and Reactivity (Part B)**

Stability:	Stable
Thermal Decomposition:	Can yield CO, CO <sub>2</sub> and organic Nitrogen compounds.
Incompatibility:	Strong acids, peroxides, and other oxidizing agents
Conditions to avoid:	Exposure to excessive heat and storage above 35°C (95°F) will shorten shelflife.

**11. Toxicological Information (Part B)**

Acute Oral Toxicity:	Not Determined
Acute Dermal Toxicity	Not Determined
Acute Inhalation Toxicity	Not Determined



**Skin Irritation:**

Corrosive to skin

The product has not been tested. The statement has been derived from the properties of the individual components.

**Eye Irritation:**

Severe damage to eyes.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Respiratory Irritation:**

Inhalation of vapors or mists may cause irritation to the respiratory system.

**Sensitization:**

May cause allergic skin reaction.

The product has not been tested. The statement has been derived from the properties of the individual components.

**Carcinogenicity Classification:**

No known carcinogen.

---

12. Ecological Information (Part B)

No Data Available

---

13. Disposal Considerations (Part B)

If the material as supplied becomes a waste, dispose in accordance with federal, state and local regulations.

---

14. Transportation Information (Part B)

DOT (US)

CARTRIDGE: Limited Quantity, LTD QTY

**\*BULK: AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III**

\*Bulk packaging in quantities of 1.3 gallons (net) or less are packaged in accordance with the limited quantity exception.

IATA/ICAO

**CARTRIDGE/BULK: AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III**

IMDG

**CARTRIDGE/BULK: AMINES, LIQUID, CORROSIVE, N.O.S. (aminoethylpiperazine, 4-Nonylphenol, branched), Class 8, UN 2735, PG III**

---

15. Regulatory Information (Part B)

HMIS Rating	
Health	*3
Flammability	1
Physical Hazard	0
PPE	B

NFPA Rating



**Hazard Rating:** 0 = minimal, 1 = Slight, 2 = moderate, 3 = severe, 4 = extreme

Federal Regulations

SARA Title 311/312

Chronic Health Hazard

CA Prop 65

Not Regulated

TSCA

Listed

State Regulations:

NJ, MA, PA

CAS#  
140-31-8

Chemical Name  
n-aminoethylpiperazine

16. Other Information

**Hazard Communication:** This SDS has been prepared in accordance with the federal OSHA Hazard Communication Standard

To the best of our knowledge, the information contained herein is accurate. However, New Enterprises Co. does not assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Additional information is available upon request.